Codice: 1H / 1ICL

Idrovernix



water-based washable paint for exterior

Water-based wall paint providing good coverage properties and a pleasant satin finish. Suitable as a topcoat for exterior walls; provides good washable properties. Formulated with weather resistant pigments. Easy to apply, this product provides a velvetlike, flexible, odourless film. The application of minimun two coats is recommended (generally slightly more diluted the first coat).

Techical Characteristics	
Paint Type	Water-based one-component
	paint
Binder type A	Acrylic
Specific gravity kg/lt (±0,05)	1.525 White
Solids content (weight) ±2	61%
Solids content (volume) ±2	42%
Shelf life +23°C (±2)	30 months in unopened cans
Note	Store in a dry and cool place.
	Do not store at low
	temperatures.
Viscosity Ford (Ø4 a 20°C)	15.000±2000 cps

Application Data	
Brush-Roller-Spray	
20-40% with water	
20-40% with water	
2 hours	
15-20 minutes (20c)	
4-24 hours	
Between +10 C and +40 C	
Less than 80%	
40-45 microns dry	
8-10	

SURFACE PREPARATION AND APPLICATION

New Plastered Walls.

The substrate should be clean, dry and pre-treated with a water-based sealer (e.g. ISOLFIX) or a solvent based sealer (e.g. FIXACRIL). Allow 4-6 hours to dry and overcoat with two coats of IDROVERNIX allowing the required waiting period between coats.

Previously Coated Walls.

Any loose or powdery old paint should be removed by wirebrushing. If necessary apply on the dry and clean surface a primer coat of water-based selaer (ISOLFIX) or solvent based sealer (FIXACRIL). Overcoat with two coats of IDROVERNIX allowing the required waiting period between coats. If the old paint is in good conditions, apply 2 coats of IDROVERNIX directly allowing the required waiting period between coats.

Colors



Colors: : BIANCO GHIACCIO

Color code:: 1H0000



Colors: : Colori Pastello Color code:: Colori Pastello









Idrovernix

SAFETY PRECAUTIONS

Before starting paint application please carefully read all the safety precautions indicated on the label of each can or in the product safety data sheet available on request. For further information please do not hesitate to contact our technical staff.

NOTES

The above information is given to the best of our current knowledge, however, because the conditions of use of our products are beyond our control, no warranty is given or to be implied in respect of such information. Our technical staff can be contacted to study customer's specific requirements involving our products in order to enable their most effective use. Dilution rates and drying times must be considered only indicative, mainly related to a temperature of 20 °C (68°F) and may vary according to prevailing temperature, in presence of particular weather conditions or depending on application procedures.





